| | | NOTE: THIS SERVICE CHECK IS BEST TO BE PERFORMED BY A TRADESPERSON Eg: Mechanic, engineer, builder, etc | Document Date: 27/10/2023, Every year, check for new service document updates at www.pilateseguip.com/instructions |
|----------------|---------------------------------------|---|--|
| 7 | 3 | If you don't understand an instruction, please contact Pilatesequip™ for a clarification | Document number: E2 27102023 |
| 1 | ۾ او | EVOLUTION REFORMER TWO - Low or Studio (use for Pilatesequip™ equipment only) | Daily |
| 9 | Š | List below: starts from the front/Foot Bar end of the Reformer, and moves through to the back. | Weekl Monthly |
| Service Beriod | Check | | Quarterly |
| _ | ĭ > | | How to fix |
| 1 (| 2 | Check that Foot Bar adjust smoothly up and down the track. | Clean any dirt from track. Use silicone spray to lubricate and slide Foot Bar back and forwards to spread the lubricate |
| 2 (| 2 | On each side of Track Adjustment Castings, check that all 4 dome nuts, on each side, are tight | Tighten bolts, re-apply Loctite |
| 2 6 | | Charly black black (Fack Day Tadasiian Machanan and and a land) into all a | Desires |
| 3 C |) | Check that the black Foot Bar Indexing Knobs are springing back into place Check that the Foot Bar Levers works and the Foot Bar rotates freely when adjusting the | Replace Lubricate ball bearings seen in-between Foot Bar Casting and Track Adjustment Casting with |
| | | angle/height. | Inox MX3, not WD40 |
| 5 (|) | Check Foot Bar Rubber doesn't rotate | Use Sikaflex 291 |
| | | Front/Spring Area | |
| 6 (|) | Check that the Jump Board Hook under the Foot Platform is not damaged | Replace |
| 7 C | 5 | Foot Strap sewing isn't coming undone Foot Strap Eyenuts are secure | Replace Reformer Foot Strap Tighten nuts |
| 9 (|) | Check Foot Platform Rubber is secured | Glue with contact adhesive |
| 10 (|) | Check Spring Attachment Buttons on the Spring Bar are secure and not damaged | Tighten hooks or re replace if damaged |
| 11 W | V | Check Stopper Pin isn't coming out of the rubber | Replace or push pin back in |
| 12 (| 2 | Check Stopper holes aren't too loose | Install new bracket |
| 13 |) | Check Stopper rubber isn't cracked | Replace |
| | | Carriage | 1 |
| 14 C |) | Clean all vinyl upholstery daily, as a minimum. Make sure you clean Shoulder Pads, Head Rest | See equipment instructions |
| | 1 | and Bed. Use a mixture of water and some ordinary mild "Sunlight Pure Soap", cut into little | |
| | 1 | flakes and placed in a spray bottle. Clean with a towel, cloth or paper towel. NOTE: Don't use other products such as chemicals, bleach, tea tree or eucalyptus oils, alcohol wipes or | |
| | | methylated spirits, or detergents- as they deteriorate vinyl. Human sweat also causes vinyl | |
| 15 C | _ | deterioration. The vinyl has an antibacterial coating and doesn't need harsh cleaners. | Pagayar Call local unhalstown |
| 16 | 2 | Check Bed upholstery for damage Shoulder Pad upholstery for damage | Recover - Call local upholsterer Replace through Pilatesequip™ or recover by calling local upholsterer |
| 17 Ç | 2 | Headrest upholstery for damage | Replace through Pilatesequip™ or recover by calling local upholsterer |
| 18 C | 5 | Check Shoulder Pad's Rod and Pin are secure and not damaged or bent Check Cleats are returning to the close position | Replace through Pilatesequip™ |
| 20 (|) | Cleats are secured to Base | Replace Tighten bolts, re-apply Loctite |
| 21 C | 2 | Head Rest is secure and hinge isn't damaged | Tighten bolts, re-apply Loctite. Replace hinge |
| 22 C | 5 | Head Rest Adjustment works with minimal or no restriction Chassis is secured to ply base - you should see 3 screw heads in each Chassis tube | Contact Pilatesequip™ Tighten bolts, re-apply Loctite |
| 24 C |) | Spring Bar under Carriage is secured to Base. | Tighten bolts, re-apply Loctite |
| 25 C | Ò | The Axles to each Running Wheel aren't bent | Replace axles |
| 26 | 5 | Check that the Wheel Bearings aren't noisy. Lift up the Carriage and spin each Running Wheel with your finger and compare them to the noise that the Guide Wheels makes. They shouldn't | Replace bearings |
| | | sound gritty. | |
| | | | - |
| 27 V | V | Springs Check all springs by slightly stretching the spring from the spring's loop at the end of the spring, | If any springs show these issues, replace spring |
| | | until the coils just start to open. If a small section of the spring barrel separates while the rest | ar any springs show these issues, replace spring |
| | | of the coils remain close, the spring is faulty. Also look for obvious bends/kinks in the spring's barrel. Make sure that spring's loops haven't travelled up the spring's coned coils | |
| 28 C | , | Springs are secure- nyloc nut are engaged/thread should be coming through the nyloc nut | Tighten |
| 29 (| 5 | Check age of springs. It's recommended to replace Reformer Springs that are older than 8 years | |
| | | | |
| | | Back of Reformer | 1 |
| 30 C |) | Check the outer layer of the rope isn't worn to the core | Replace |
| 31 (| 5 | Rope clips. Check the Rope Clips pivot point. Check that the swivel/pivot head isn't worn, where the clip's body attaches itself to the ring. | Replace |
| 32 C | 2 | Hand strap sewing isn't coming undone | Replace |
| 22 | | Charle Dullaye not point. Bull either side of the year to make his Bullion may and 2 and | |
| 33 (| 2 | Check Pulleys not noisy. Pull either side of the rope to make the Pulley run and listen for a rough noise | Replace Pulley |
| 34 C | 2 | Pulleys attachment to eyenuts are tight | Tighten |
| 35 (|) | | |
| 36 | _ | Uprights secured to frame | Tighten |
| |) | | |
| | 2 | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks | Tighten Contact Pilatesequip™ |
| 37 V | V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and |
| 37 V | V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks | Tighten Contact Pilatesequip™ |
| | V | Uprights secured to frame | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch- |
| 38 V | V | Uprights secured to frame | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad |
| | V 4 | Uprights secured to frame | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch- |
| 38 V | V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions |
| 38 W | V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | 4 | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |
| 38 W | V V V V V V V V V V V V V V V V V V V | Uprights secured to frame Pulleys Upright mechanism to lower and lock is working with no restriction Frame and Tracks Clean wheels to reduce dirt build up. Clean tracks to reduce dirt build up. Lubricate running surface of the Tracks after cleaning Check frame structure has no gaps where Rails meet Legs | Tighten Contact Pilatesequip™ Clean Wheels by wiping with damp rag. Place rag on Wheel and move the Carriage back and forth. If there's built-up dirt, lightly rub with a fine green Scotch-Brite pad Clean Tracks by wiping with damp rag. Wipe the front and the back of the Tracks, by moving the Carriage back and forth. If there's built-up dirt balls, lightly rub with a fine green Scotch-Brite pad Use dry silicone spray only and it's follow instructions Contact Pilatesequip™ with photos |